



435100 Baia Sprie, str. Piersicului nr. 24

tel. 0262 262 111 ; 0722 425 088

[www.florisol.ro](http://www.florisol.ro) office@florisol.ro

Pt. comenzi : 0742-478468 ; 0753 050 066

### Preturi Ghivece productie 2021.2 / PALET

Ghiveci Dimensiune	Pret/ buc Negru	Pret/ buc Maro	Pret/ buc Alb	Pret/ buc color	Nr.buc./ palet
BT 8.5	0.11	0.12	0.15	0.19	38700
BT 9	0.12	0.13	0.16	0.22	30960
BT 10	0.15	0.16	0.19	0.28	23040
BTS 10.5	0.17	0.19	0.20	0.27	22950
BTSL 10.5	0.18	0.20	0.22	0.29	22140
BTS 11	0.19	0.21	0.23	0.30	20592
BTSL11	0.20	0.22	0.26	0.35	19656
BTS 12	0.21	0.23	0.29	0.39	14580
BT 13	0.30	0.32	0.40	0.54	11016
SK 15	0.43	0.46	0.53	0.70	9800
SK 17	0.50	0.54	0.62	0.85	8200
SK 19	0.70	0.74	0.89	1.23	5280
SK 23	1.10	1.2	1.30	1.83	3680
Bol M 17	0.50	0.50	0.58	0.75	11520
Bol M 19	0.66	0.66	0.73	0.95	8400
Bol M 21	0.85	0.85	1.00	1.38	5520
Agatator Z 46/Z 36	0.48	0.48	0.55	0.67	9000
Suspendat W 25	1.67	1.67	1.88	2.46	3240
Suspendat W 23	1.38	1.38	1.55	2.10	4600
Suspendat W 21	1.26	1.26	1.29	1.57	5600

**Mențiuni:**

- Comanda minima este de 1 palet / sortiment
- Prețurile includ TVA și transportul la beneficiar

*Pentru detalii și informații nu ezitați să ne contactați.*

**Comenzi: tel. 0742 478 468 ; 0753 050 066**

*Aceste prețuri sunt valabile la achiziția unui palet complet!!*

## Descrierea ghivecelor si modul de ambalare

Produs	Inclinatie	Diametru	Inaltime	Volum	Nr. buc./ bax	Nr. bax / palet	Nr. buc. / palet
-							
BT 8.5	5°	85 mm	65 mm	0,22 l	2 150	18	38 700
BT 9	5°	90 mm	68 mm	0,30 l	1720	18	30 960
BT 10	5°	100 mm	76 mm	0,41 l	1280	18	23 040
BTS 10.5	5°	105 mm	80 mm	0,46 l	1275	18	22 950
BTSL 10.5	5°	105 mm	92 mm	0,51 l	1230	18	22 140
BTS 11	5°	110 mm	82 mm	0,50 l	1144	18	20 592
BTSL11	5°	110 mm	95 mm	0,60 l	1092	18	19 656
BTS 12	5°	120 mm	90 mm	0,72 l	810	18	14 580
BT 13	5°	130mm	98 mm	0,85 l	612	18	11 016
M 17		170mm	85 mm	1,60 l	80	144	11520
M 19		190 mm	95 mm	2,10 l	75	112	8400
M 21		210 mm	105 mm	3,0 l	60	92	5520
SK 15	5°	150 mm	120 mm	1,5 l	50	196	9800
SK 17	5°	170 mm	133 mm	2 l	50	164	8200
SK 19	5°	190 mm	148 mm	3 l	40	132	5280
SK 23	5°	230 mm	180 mm	5 l	40	92	3 680
W21		220 mm	144 mm	3 l	40	140	5 600
W23		230 mm		4 l	40	115	4 600
W 25		250 mm	152 mm	5 l	60	54	3240
Z36			360 mm		20/500	18	9 000
Z46			470 mm		20/500	18	9 000